



TECHNICAL DATA SHEET

DRW300 Extra-strong universal paint stripper methylene-chloride free

Description	Extra-strong universal paint stripper for metal surfaces, wood, masonry. Suitable for vertical application too.
Main uses	It removes polyurethane, alkyd, epoxy, polyester, acrylic, nitrocellulose paints, and glues for wood too. It is effective on thick and aged layers and it is eccellente in refinish of furniture and for boats. It is not suitable for car refinishing.
Instructions for use	Cautiously open the sealed cap, along from face. Mix the product abundantly with a spatula, lay on the surface a thick layer. Wait the necessary time: 5-15 min for nitrocellulose / alkyd short-oil coatings; 1-2 h for PU and acrylics, 4-8 h for polyester coatings. It is deprecated to use the product on sun-exposed or howsoever hot surfaces. Before use carefully read the hazard label paying special care to the precautionary statements.

TECHNICAL DATA

Physical State	thixotropic gel - turquoise		
Odour	mild, sweetish, of solvents		
Flashpoint	< 21	°C	
Density	0,98 (± 0,1)	kg/L	approx.
Yield	≈ 2 m ² /L		
pH	neutral / not applicable		
T application	> 5 °C < 35 °C		
Evaporation speed	very slow		

NOTE

Keep container tightly closed. Store in a well-ventilated area. Keep away from sources of ignition.